

AIR ANGLE & VERTICAL SANDER



GP-829



▶ Rear Exhaust
 ▶ Gravity Cast
GP-929



GP-821



GP-823G

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Pad Size (inch)	Spindle Thread (inch)	Free Speed (rpm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet (inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-829	7"	5/8"-11,M14	4,500	1.90	370	0.43	1/4"	6.5	86	< 2.5	10 pcs/1.95 cu-ft/G.W.: 24.5 kgs
GP-929	7"	5/8"-11,M14	4,500	2.90	441	0.45	1/4"	6.5	81	< 2.5	6 pcs/1.65 cu-ft/G.W.: 19 kgs
GP-821	7"	5/8"-11	4,200	2.60	190	0.70	1/4"	6.5	88	< 2.5	8 pcs/1.2 cu-ft/G.W.: 22.5 kgs
GP-823G	3", 4-1/2", 5-1/2"	--	16,000	1.20	165	0.56	1/4"	6.5	95	2.9	10 pcs/1.0 cu-ft/G.W.: 14 kgs

MINI AIR ANGLE SANDER



▶ No Gear
 ▶ Rear Exhaust
GP-824RS2
GP-824RS3



GP-824STA3



GP-823A



▶ 110°
GP-824MA



▶ 110°
 ▶ No Gear
GP-824CF



▶ Composite ▶ No Gear
 ▶ Rear Exhaust ▶ 100°
GP-823AR
GP-823AR3



▶ Composite ▶ No Gear
 ▶ Rear Exhaust ▶ 100°
GP-823AR5



GP-822A



GP-822C



▶ 110°
GP-824LS



▶ Composite ▶ 100°
 ▶ Rear Exhaust ▶ No Gear
GP-824LSR

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm²)

Model	Type	Pad Size (inch)	Diameter Orbit (mm)	Free Speed (rpm)	Net Weight (kgs)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet (inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec ²)	Packing
GP-824RS2	Rotate	2"	--	22,000	0.36	155	0.70	1/4"	5.0	89	< 2.5	20 pcs/1.0 cu-ft/G.W.: 9.0 kgs
GP-824RS3	Rotate	3"	--	22,000	0.37	155	0.70	1/4"	5.0	89	< 2.5	20 pcs/1.0 cu-ft/G.W.: 9.0 kgs
GP-823STA3	Rotate	2"	--	15,000	0.70	178	0.62	1/4"	5.0	86	< 2.5	12 pcs/0.8 cu-ft/G.W.: 11.5 kgs
GP-823A	Rotate	2"	--	15,000	0.66	152	0.56	1/4"	5.0	85	< 2.5	20 pcs/0.95 cu-ft/G.W.: 14 kgs
GP-824MA	Rotate	2"	--	15,000	0.66	170	0.56	1/4"	5.0	86	< 2.5	10 pcs/1.2 cu-ft/G.W.: 13.5 kgs
GP-824CF	Rotate	2"	--	25,000	0.65	142	0.30	1/4"	5.0	82	< 2.5	10 pcs/1.2 cu-ft/G.W.: 13.5 kgs
GP-823AR	Rotate	2"	--	22,000	0.55	170	0.53	1/4"	5.0	79	< 2.5	10 pcs/1.0 cu-ft/G.W.: 9 kgs
GP-823AR3	Rotate	3"	--	15,000	0.70	180	0.49	1/4"	6.0	78	< 2.5	20 pcs/1.1 cu-ft/G.W.: 15 kgs
GP-823AR5	Rotate	5"	--	3,000	0.88	178	0.48	1/4"	6.5	70	< 2.5	20 pcs/1.6 cu-ft/G.W.: 25 kgs
GP-822A	Dual Action	2"	3	15,000	0.70	152	0.42	1/4"	5.0	85	< 2.5	25 pcs/2.2 cu-ft/G.W.: 19 kgs
GP-822C	Dual Action	3"	1	16,000	0.76	180	0.32	1/4"	5.0	95	< 2.5	25 pcs/0.7 cu-ft/G.W.: 20 kgs
GP-824LS	Dual Action	2" or 3"	3	15,000	0.70	165	0.45	1/4"	5.0	87	< 2.5	25 pcs/1.7 cu-ft/G.W.: 20 kgs
GP-824LSR	Dual Action	2"	3	13,000	0.65	180	0.42	1/4"	6.0	77	< 2.5	20 pcs/1.1 cu-ft/G.W.: 14 kgs