

# AIR JITTERBUG SANDER (SQUARE TYPE)



Self-Generated Vacuum  
GP-934SD



Non-Vacuum  
GP-827N



Non-Vacuum  
GP-937S



Non-Vacuum  
GP-926



Non-Vacuum  
GP-927

# AIR ORBITAL DELTA SANDER (TRIANGLE TYPE)



Non-Vacuum  
GP-938DN



Central Vacuum  
GP-938DC



Self-Generated Vacuum  
GP-938DS

# STRAIGHT LINE AIR SANDER



GP-845A

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm<sup>2</sup>)

Model	Pad Size	Free Speed (rpm)	Diameter Orbit (mm)	Net Weight (kgs)	Length (mm)	Air Cons. (m <sup>3</sup> /min)	Air Inlet (inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec <sup>2</sup> )	Packing
GP-934SD	93x176 mm	6,000	5	2.10	275	0.40	1/4"	6.5	87	9.2	6 pcs/2.0 cu-ft/G.W.: 18 kgs
GP-827N	88x165 mm	8,000	1.8	1.80	170	0.42	1/4"	6.5	88	9.0	10 pcs/1.34 cu-ft/G.W.: 20 kgs
GP-937S	74x145 mm	8,000	5	1.20	155	0.34	1/4"	6.5	81	11.0	12 pcs/1.3 cu-ft/G.W.: 17 kgs
GP-926	75x82 mm	15,000	1.2	0.50	140	0.15	1/4"	5.0	77	5.4	20 pcs/1.3 cu-ft/G.W.: 18 kgs
GP-927	100x110 mm	20,000	1.6	0.55	130	0.31	1/4"	5.0	84	7.2	20 pcs/2.3 cu-ft/G.W.: 20.5 kgs

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm<sup>2</sup>)

Model	Free Speed (rpm)	Net Weight (kgs)	Air Cons. (m <sup>3</sup> /min)	Air Inlet (inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec <sup>2</sup> )	Packing
GP-938DN	10,000	0.9	0.31	1/4"	10	80	< 2.5	10 pcs/1.2 cu-ft/G.W.: 10 kgs
GP-938DC	10,000	0.9	0.31	1/4"	10	80	< 2.5	10 pcs/1.2 cu-ft/G.W.: 10 kgs
GP-938DS	10,000	1.5	0.31	1/4"	10	80	< 2.5	10 pcs/1.2 cu-ft/G.W.: 10 kgs

**Random Orbital** Diameter Orbit 3.2 mm

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm<sup>2</sup>)

Model	Pad Size (mm)	Stroke Length (mm)	Stroke Speed (bpm)	Net Weight (kgs)	Length (mm)	Air Cons. (m <sup>3</sup> /min)	Air Inlet (inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec <sup>2</sup> )	Packing
GP-845A	70x445	25	2,100	3.00	450	0.35	1/4"	6.5	91	19.0	5 pcs/1.3 cu-ft/G.W.: 15 kgs