

# AIR RATCHET WRENCH 1/2", 3/8"



▶ Stubby Type  
GP-855H



GP-855F



GP-855B 3/8"  
GP-856B 1/2"



GP-857



GP-855D 3/8"  
GP-856D 1/2"



GP-855R1 3/8"  
GP-856R1 1/2"



GP-855G 3/8"  
GP-856G 1/2"



GP-855GR 3/8"  
GP-856GR 1/2"



▶ Low Recoil  
GP-855J2 3/8"  
GP-856J2 1/2"



▶ Ratchet Head Adjustable  
GP-855AD 3/8"  
GP-856AD 1/2"



▶ Quick Change Socket  
GP-855Q 3/8"  
GP-856Q 1/2"

Specifications

Recommended Air Pressure 90 psi (6.3 kg/cm<sup>2</sup>)

Model	Square Drive (inch)	Max. Working Torque ft.lb(Nm)	Net Weight (kgs)	Length (mm)	Air Cons. (m <sup>3</sup> /min)	Air Inlet (inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec <sup>2</sup> )	Packing
GP-855H	3/8"	22(30)	0.50	125	0.37	1/4"	6.5	86	< 2.5	30 pcs/0.7 cu-ft/G.W.: 16 kgs
GP-855F	3/8"	37(50)	0.64	165	0.49	1/4"	6.5	87	< 2.5	30 pcs/0.7 cu-ft/G.W.: 21 kgs
GP-855B	3/8"	50(68)	0.97	254	0.54	1/4"	6.5	98	< 2.5	20 pcs/0.7 cu-ft/G.W.: 24 kgs
GP-856B	1/2"	50(68)	0.97	254	0.56	1/4"	6.5	98	< 2.5	20 pcs/0.7 cu-ft/G.W.: 24 kgs
GP-857	1/2"	90(122)	2.00	360	0.63	1/4"	6.5	103	5.3	10 pcs/0.57 cu-ft/G.W.: 22 kgs
GP-855D	3/8"	50(68)	1.20	265	0.49	1/4"	6.5	86	< 2.5	12 pcs/1.1 cu-ft/G.W.: 16.5 kgs
GP-856D	1/2"	50(68)	1.20	265	0.49	1/4"	6.5	86	< 2.5	10 pcs/1.1 cu-ft/G.W.: 16.5 kgs
GP-855R1	3/8"	60(82)	1.20	270	0.49	1/4"	6.5	74	3.0	20 pcs/0.68 cu-ft/G.W.: 26 kgs
GP-856R1	1/2"	60(82)	1.20	270	0.49	1/4"	6.5	74	3.0	20 pcs/0.66 cu-ft/G.W.: 28 kgs
GP-855G	3/8"	50(68)	1.3	294	0.45	1/4"	6.5	87	< 2.5	10 pcs/0.9 cu-ft/G.W.: 15 kgs
GP-856G	1/2"	50(68)	1.3	294	0.45	1/4"	6.5	87	< 2.5	10 pcs/0.9 cu-ft/G.W.: 15 kgs
GP-855GR	3/8"	90(122)	1.2	267	0.63	1/4"	6.5	90	< 2.5	20 pcs/1.2 cu-ft/G.W.: 25 kgs
GP-856GR	1/2"	90(122)	1.2	267	0.63	1/4"	6.5	90	< 2.5	20 pcs/1.2 cu-ft/G.W.: 25 kgs
GP-855J2	3/8"	60(82)	1.30	265	0.49	1/4"	6.5	87	< 2.5	20 pcs/1.7 cu-ft/G.W.: 30 kgs
GP-856J2	1/2"	60(82)	1.20	270	0.49	1/4"	6.5	74	3.0	20 pcs/0.66 cu-ft/G.W.: 28 kgs
GP-855AD	3/8"	50(68)	1.30	260	0.52	1/4"	6.5	87	< 2.5	20 pcs/1.7 cu-ft/G.W.: 28 kgs
GP-856AD	1/2"	50(68)	1.30	260	0.49	1/4"	6.5	87	< 2.5	20 pcs/1.7 cu-ft/G.W.: 28 kgs
GP-855Q	3/8"	60(82)	1.30	254	0.63	1/4"	6.5	95	< 2.5	20 pcs/1.2 cu-ft/G.W.: 26 kgs
GP-856Q	1/2"	60(82)	1.30	254	0.63	1/4"	6.5	95	< 2.5	20 pcs/1.2 cu-ft/G.W.: 26 kgs

# AIR RATCHET WRENCH 1/4"



▶ Stubby Type  
**GP-854H**



**GP-854F**



▶ Thru-Hole Type  
**GP-854J**



▶ Thru-Hole Type  
**GP-854J2**



**GP-854**



**GP-854D**

Specifications										Recommended Air Pressure 90 psi (6.3 kg/cm <sup>2</sup> )
Model	Square Drive (inch)	Max. Working Torque ft.lb(Nm)	Net Weight (kgs)	Length (mm)	Air Cons. (m <sup>3</sup> /min)	Air Inlet (inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/sec <sup>2</sup> )	Packing
GP-854H	1/4"	22(30)	0.50	125	0.37	1/4"	6.5	86	< 2.5	30 pcs/0.7 cu-ft/G.W.: 16 kgs
GP-854F	1/4"	37(50)	0.64	165	0.49	1/4"	6.5	87	< 2.5	30 pcs/0.7 cu-ft/G.W.: 21 kgs
GP-854	1/4"	30(40)	0.50	170	0.49	1/4"	6.5	90	< 2.5	20 pcs/0.37 cu-ft/G.W.: 11.2kgs
GP-854D	1/4"	30(40)	0.54	174	0.54	1/4"	6.5	72	< 2.5	20 pcs/0.64 cu-ft/G.W.: 15.9 kgs
GP-854J	1/4"	30(41)	0.60	210	0.54	1/4"	6.5	85	< 2.5	20 pcs/1.1 cu-ft/G.W.: 17 kgs
GP-854J2	1/4"	30(41)	0.50	167	0.54	1/4"	6.5	83	< 2.5	20 pcs/1.1 cu-ft/G.W.: 15 kgs

# AIR RATCHET WRENCH KITS



**GP-855BK**



**GP-855DK**



**GP-856BK**



**GP-856DK**

GP-855BK		GP-855DK		GP-856BK		GP-856DK	
1 pc	3/8" Air Ratchet Wrench (GP-855B)	1 pc	3/8" Air Ratchet Wrench (GP-855D)	1 pc	1/2" Air Ratchet Wrench (GP-856B)	1 pc	1/2" Air Ratchet Wrench (GP-856D)
7 pcs	Socket	7 pcs	Socket	7 pcs	Socket	7 pcs	Socket
1 pc	Universal Joint	1 pc	Universal Joint	1 pc	Universal Joint	1 pc	Universal Joint
2 pcs	Adapter	1 pc	75mm Extension Bar	2 pcs	Adapter	1 pc	75mm Extension Bar
1 pc	Nipple	1 pc	Nipple	1 pc	Nipple	1 pc	Nipple
3 pcs	Bit	1 pc	Oil Pot	3 pcs	Bit	1 pc	Oil Pot
1 pc	Oil Pot	1 pc	Blow Case	1 pc	Oiler Pot	1 pc	Blow Case
1 pc	Plastic Box			1 pc	Plastic Box		
Packing 5 sets/0.75 cu-ft/G.W.: 13.5 kgs		Packing 6 sets/1.3 cu-ft/G.W.: 15 kgs		Packing 5 sets/0.75 cu-ft/G.W.: 13.5 kgs		Packing 6 sets/1.3 cu-ft/G.W.: 15 kgs	