

AIR STAPLER



| Specifications | | Recommended Air Pressure 60 ~ 100 psi | | | | | | | |
|----------------|-------|---------------------------------------|---|--------------------------|--------------------|------------------|----------------------|---------------------------------|-------------------------------|
| Model | Gauge | Crown (mm) | Staple Size W.x T.x L.(mm) | Tool Size L.x H.x W.(mm) | Load Capacity (pc) | Net Weight (kgs) | Sound Pressure (dBA) | Vibration (m/sec ²) | Packing |
| GP-71/16K | 22 | 9.1 | 0.75 x 0.60 x (6-16) | 200 x 147 x 42 | 100 | 0.96 | 77.4 | 1.10 | 10 pcs/0.9 cu-ft/G.W.: 11 kgs |
| GP-80/16K | 21 | 12.8 | 0.95 x 0.65 x (6-16) | 200 x 147 x 42 | 100 | 0.96 | 77.4 | 1.10 | 10 pcs/0.9 cu-ft/G.W.: 11 kgs |
| GP-80/25K | 21 | 12.8 | 0.65 x 0.95 x (10-25) | 240 x 177 x 51 | 100 | 1.10 | 79.8 | 2.12 | 10 pcs/1.2 cu-ft/G.W.: 13 kgs |
| GP-90/25K | 18 | 5.8 | 1.00 x 1.25 x (10-25) | 240 x 177 x 51 | 100 | 1.10 | 78.9 | 2.12 | 10 pcs/1.2 cu-ft/G.W.: 13 kgs |
| GP-90/40K | 18 | 5.8 | 1.00 x 1.25 x (10-40) | 310 x 270 x 77 | 100 | 2.18 | 82.8 | 3.06 | 5 pcs/1.5 cu-ft/G.W.: 16 kgs |
| GP-50/40K | 18 | 5.8 | Stapler: 1.00 x 1.25 x (10-40) Nailer: 1.00 x 1.25 x (15-50) | 237 x 237 x 50 | 100 | 1.70 | 78.8 | 2.86 | 10 pcs/1.4 cu-ft/G.W.: 18 kgs |

AIR NAILER /PINNER



| Specifications | | Recommended Air Pressure 100 psi | | | | | | | |
|----------------|-------|---|--------------------------|--------------------|------------------|----------------------|---------------------------------|--------------------------------|--|
| Model | Gauge | Nail Size W.x T.x L.(mm) | Tool Size L.x H.x W.(mm) | Load Capacity (pc) | Net Weight (kgs) | Sound Pressure (dBA) | Vibration (m/sec ²) | Packing | |
| GP-16/50K | 16 | 1.60 x 1.40 x (20-50) | 310 x 270 x 77 | 100 | 2.18 | 81.1 | 3.00 | 5 pcs/1.5 cu-ft/G.W.: 16 kgs | |
| GP-16/64K | 16 | 1.60 x 1.40 x (25-64) | 295 x 303 x 92 | 100 | 2.48 | 83.0 | 3.06 | 5 pcs/2.7 cu-ft/G.W.: 18 kgs | |
| GP-F18/30K | 18 | 1.20 x 1.00 x (10-30) | 235 x 197 x 55 | 100 | 1.20 | 76.7 | 1.94 | 10 pcs/1.2 cu-ft/G.W.: 13 kgs | |
| GP-F18/50K | 18 | 1.20 x 1.00 x (15-50) | 205 x 240 x 55 | 100 | 1.40 | 79.0 | 2.40 | 10 pcs/1.5 cu-ft/G.W.: 16 kgs | |
| GP-T64K | 14 | 2.20 x 1.65 x (15-64) | 300 x 270 x 100 | 80 | 2.50 | 85.0 | 3.00 | 5 pcs/2.7 cu-ft/G.W.: 18 kgs | |
| GP-P0.6/25K | 23 | 0.64 x 0.64 x (12-25) | 225 x 152 x 45 | 200 | 1.00 | 73.4 | 1.05 | 10 pcs/1.17 cu-ft/G.W.: 12 kgs | |
| GP-CF15K | | Crown x T.x L.(mm): 2.54 x 2.20 x (9,12,15) | 300 x 270 x 87 | 80 | 2.66 | 85.0 | 4.40 | 5 pcs/2.7 cu-ft/G.W.: 18 kgs | |
| GP-90/21K | | Shank Type: Smooth, Screw, Ring Shank Dia.: 2.87, 3.05, 3.33 mm Round Head, Collated: Plastic | 478 x 350 x 127 | 105 | 3.80 | 92.4 | 4.40 | 1 pc/1 cu-ft/G.W.: 4.5 kgs | |